

Electric Chain Hoist NOVA Blackline

Product information



General: The NOVA Blackline meets the high demands of a SWF hoist in regards to safety, quality and reliability.

- Ultimate load from 2-12,5 tons and a lifting weight up to 12 meters
- Optimal space and land utilization due to compact headroom and optimum hook dimension
- Minimized attrition of rope by a big drum diameter
- Robust contactor control for hoist motor and trolley motor
- Mechanical overload protection protects crane and building structure
- Plug and play - quick and easy installation and maintenance
- Overheat protection

| Part Code | Code | Lifting height m | Max load kg | FEM | Lifting speed m/min. | ISO | Trolley speed m/min | Delivery time |
|-----------|---------|---------------------|----------------|-----|-------------------------|-----|------------------------|---------------|
| 6041 | NOVA BB | 6 | 2,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BB | 9.5 | 2,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BB | 6 | 2,500 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BB | 9.5 | 2,500 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BB | 6 | 3,200 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BB | 9.5 | 3,200 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BC | 6 | 4,000 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BC | 9 | 4,000 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BC | 6 | 5,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BC | 9 | 5,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BC | 6 | 6,300 | 1Am | 4/0,7 | M4 | 20/5 | 20 |
| 6041 | NOVA BC | 9 | 6,300 | 1Am | 4/0,7 | M4 | 20/5 | 20 |
| 6041 | NOVA BD | 9 | 8,000 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BD | 12 | 8,000 | 3m | 5/0,8 | M6 | 20/5 | 20 |
| 6041 | NOVA BD | 9 | 10,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BD | 12 | 10,000 | 2m | 5/0,8 | M5 | 20/5 | 20 |
| 6041 | NOVA BD | 9 | 12,500 | 1Am | 4/0,7 | M4 | 24/6 | 20 |
| 6041 | NOVA BD | 12 | 12,500 | 1Am | 4/0,7 | M4 | 24/6 | 20 |