



## Ferrule K Talurit®

### Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

**Material:** Aluminum

**Marking:** According to standard

**Standard:** Talurit splicing system

*The ferrules do not correspond to standard EN 13411-3 but have been tested and verified by Talurit.*

**Note:** See the manufacturer's product data sheet below for guidance on dimension selection.

<b>Part Code</b>	<b>Ferrule size mm</b>	<b>Length mm</b>	<b>Delivery time</b>
120100900030	9	36	20
120101000030	10	41	2
120101100030	11	45	20
120101200030	12	50	2
120101300030	13	55	20
120101400030	14	59	2
120101600030	16	64	2
120101800030	18	73	2
120102000030	20	82	2
120102200030	22	91	20
120102400030	24	100	20
120102600030	26	109	20
120102800030	28	118	20
120103000030	30	127	20
120103200030	32	136	20
120103400030	34	146	20
120103600030	36	155	20
120103800030	38	164	20
120104000030	40	173	20
120104200030	42	182	20
120104400030	44	191	20