



## Horizontal Lifting Clamp THSK

### Product information

Lifting clamp with adjustable extra large jaw opening for horizontal lifting, handling and transporting of stacks, packages and single steel plates. Terrier THSK lifting clamps must always be used in pairs (or multiple pairs). The adjustable jaw offers wide variety of openings available from 3 to 420 mm.

#### Features:

- Easy adjustable jaw opening
- Quick and easy placing and removing of the clamp
- Lightweight design for easy handling
- Tough quality heavy duty welded body

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

**Temperature range:** - 40°C up to +100°C.

**Standard:** EN 13155

**Note:** The lifting clamps are suitable for lifting and transporting of steel plates with a maximum hardness of 37 HRC (345 HB, 1166 N/mm<sup>2</sup>). The lifting clamps must always be used in pairs (or multiple pairs).

**Warning:** Hardness level of the material surface may not exceed 37 HRC (345 Hb, 1166 N/mm<sup>2</sup>)

Part Code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	T mm	H mm	U mm	X mm	Y mm	Z mm	Weight kg	Delivery time
502100151800700	1.5 THSK/180	1.5	3-180	201	135	15	30,5	18	289	90	20	60	9.5	7
502100153000700	1.5 THSK/300	1.5	3-300	201	135	15	30,5	18	409	90	20	60	11	7
502100301800700	3 THSK/180	3	3-180	241	165	20	30,5	18	296	105	20	69	13	7
502100303000700	3 THSK/300	3	3-300	241	165	20	30,5	18	416	105	20	69	15	7
502100451800700	4.5 THSK/180	4.5	3-180	241	165	20	30,5	18	296	105	20	69	13	7
502100454200700	4.5 THSK/420	4.5	3-420	241	165	20	30,5	18	536	105	20	69	17	7
502100601800700	6 THSK/180	6	3-180	256	160	25	30,5	18	304	120	20	75	18	7
502100604200700	6 THSK/420	6	3-420	256	160	25	30,5	18	544	120	20	75	24	7
502100901800700	9 THSK/180	9	3-180	256	160	25	30,5	18	304	120	20	75	18	7
502100904200700	9 THSK/420	9	3-420	256	160	25	30,5	18	544	120	20	75	24	7

## Blueprint

