



Eye Grab Hook X-041

Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Painted.

Standard: EN 1677-1

Note: Not for use with Omega Link

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | A mm | B mm | F mm | G mm | K mm | P mm | Weight kg | Delivery time |
|--------------|-------------------|---------|------|------|------|------|------|------|-----------|---------------|
| 402300140740 | 6 | 1.4 | 13 | 7 | 26 | 8 | 50 | 8 | 0.2 | 20 |
| 402300250740 | 7-8 | 2.5 | 16 | 10 | 30 | 9 | 62 | 10 | 0.3 | 2 |
| 402300400740 | 10 | 4 | 20 | 13 | 40 | 13 | 82 | 13 | 0.6 | 2 |
| 402300670740 | 13 | 6.7 | 26 | 16 | 52 | 16 | 107 | 17 | 1.4 | 2 |
| 402301000740 | 16 | 10 | 30 | 18 | 70 | 20 | 132 | 21 | 2.4 | 20 |
| 402301600740 | 20 | 16 | 40 | 22 | 73 | 24 | 148 | 24 | 4 | 20 |
| 402301900740 | 22 | 19 | 42 | 24 | 86 | 26 | 166 | 26 | 5 | 20 |
| 402302650740 | 26 | 26.5 | 50 | 30 | 110 | 32 | 207 | 33 | 10.1 | 20 |

Blueprint

