



Double Swivel Lifting Ring Codipro Giga DSS

Product information

The universal swivel shackle GIGA DSS is a double swivel ring. It is specially designed for simultaneously lifting androtating of very heavy loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Swiveling under load
- Usable for any kind of heavy lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range.

Material: High tensile steel Marking: According to standard, CE-marked Temperature range: -20°C up to +200°C Standard: EN 1677-1 except grade/WLL

Safety factor: 5:1

Part Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S1 mm	S2 mm	Weight kg	Delivery time
4215GIGADSSM150UP	125	M 150 (x6)	2,000	271	115	290	353	302	544	103	228	41	105	268	17

Technical data

5:1	METRIC THREADS	Torque (Nm)	-		L		L	L		B L	B L	
	Number of rings		1	2		2		2			3 → 4	
	Lifting angle β		0°	0°	0 °	0 °	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric
	Loading angle α		0°	0 °	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
	MEGA.DSS+ M 64 UP	600	30,00	60,00	30,00	60,00	42,00	30,00	30,00	63,00	45,00	30,00
	MEGA.DSS+ M 72 UP	700	35,00	70,00	35,00	70,00	49,00	35,00	35,00	73,50	52,50	35,00
+	MEGA.DSS+ M 72x4 UP	700	35,00	70,00	35,00	70,00	49,00	35,00	35,00	73,50	52,50	35,00
Ξ.	MEGA.DSS+ M 80 UP	800	40,00	80,00	40,00	80,00	56,00	40,00	40,00	84,00	60,00	40,00
max. load	MEGA.DSS+ M 90 UP	900	50,00	100,00	50,00	100,00	70,00	50,00	50,00	105,00	75,00	50,00
	MEGA.DSS+ M 100 UP	1000	60,00	120,00	60,00	120,00	84,00	60,00	60,00	126,00	90,00	60,00
		2000	125,00	250,00	125,00	250,00	175,00	125,00	125,00	262,50	187,50	125,00
	GIGA.DSS+Q M 150 UP	160	125,00	250,00	125,00	250,00	175,00	125,00	125,00	262,50	187,50	125,00

Blueprint



