

Elevator rope 8x19S-FC

Product information



General: Steel wire rope for use in elevator.

Tolerance: ≤10 mm 0% - +6%, 10 mm 0% - +5%.

Rope construction: 8x19S-FC, Seal.


Marking: According to standard

Finish: Ungalvanised.

Standard: EN 12385-5

Fill factor: 0.44

Elevator



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm ²	Lubrication	Weight kg/100m	Delivery time
106100804130209	8	1,370/1,770	Bright	sZ	28.1	22	SupplierStandard	22.2	2
106100904130209	9	1,370/1,770	Bright	sZ	35.6	28.3	SupplierStandard	28	20
106101004130209	10	1,370/1,770	Bright	sZ	44	34.9	SupplierStandard	34	2
106101104130209	11	1,370/1,770	Bright	sZ	53.2	42.2	SupplierStandard	41	2
106101204130209	12	1,370/1,770	Bright	sZ	63.3	50.3	SupplierStandard	49	20
106101304130209	13	1,370/1,770	Bright	sZ	74.3	59	SupplierStandard	58	20
106101404130209	14	1,370/1,770	Bright	sZ	86.1	68.4	SupplierStandard	67	20
106101504130209	15	1,370/1,770	Bright	sZ	98.9	78.5	SupplierStandard	77	20
106101604130209	16	1,370/1,770	Bright	sZ	113	89.3	SupplierStandard	87	20