

Lifting Point 8-211 Long bolt



Product information



- Rotates through 360° and pivot 90°
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

Features: Built-in RFID/NFC chip

Material: Alloy steel, quenched and tempered

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

| Part Code | WLL ton | Torque Nm | Thread M mm | Thread length (E) mm | Pitch DIN13 | A mm | B mm | C mm | D mm | F mm | G mm | SW mm | J mm | K mm | L mm | N mm | Weight kg | Delivery time |
|-----------------|---------|-----------|-------------|----------------------|-------------|------|------|------|------|------|------|-------|------|------|------|------|-----------|---------------|
| 42158211003105L | 0.3 | 30 | M 8 | 76 | 1.25 | 30 | 35 | 35 | 11 | 86 | 55 | 13 | 77 | 34 | 41 | 24 | 0.4 | 20 |
| 42158211006125L | 0.63 | 60 | M 10 | 96 | 1.5 | 30 | 35 | 36 | 11 | 86 | 55 | 17 | 78 | 34 | 40 | 24 | 0.4 | 20 |
| 42158211010150L | 1 | 100 | M 12 | 114 | 1.75 | 33 | 38 | 44 | 14 | 99 | 57 | 19 | 89 | 38 | 42 | 31 | 0.5 | 20 |
| 42158211015185L | 1.5 | 150 | M 16 | 149 | 2 | 33 | 38 | 46 | 14 | 99 | 57 | 24 | 89 | 38 | 40 | 31 | 0.7 | 20 |
| 42158211025230L | 2.5 | 250 | M 20 | 186 | 2.5 | 50 | 54 | 56 | 16 | 142 | 82 | 30 | 132 | 53 | 70 | 49 | 1.7 | 20 |
| 42158211040265L | 4 | 400 | M 24 | 221 | 3 | 50 | 54 | 59 | 16 | 143 | 82 | 36 | 132 | 53 | 67 | 45 | 2 | 20 |
| 42158211050340L | 5 | 500 | M 30 | 278 | 3.5 | 60 | 65 | 81 | 23 | 170 | 99 | 46 | 153 | 64 | 67 | 59 | 2.9 | 20 |
| 42158211100350L | 10 | 1,000 | M 42 | 272 | 4.5 | 77 | 85 | 104 | 27 | 225 | 124 | 65 | 204 | 79 | 94 | 69 | 7.9 | 20 |

Blueprint

