



Master link, grade 80

Product information

Masterlink for chain sling assemblies.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | EWL mm | For chain mm, 1-leg | For chain mm, 2-leg | A mm | B mm | D mm | Weight kg | Delivery time |
|--------------|---------|--------|---------------------|---------------------|------|------|------|-----------|---------------|
| 401100160260 | 1.6 | 110 | 6/7 | 6 | 110 | 60 | 13 | 0.34 | 5 |
| 401100210260 | 2.12 | 110 | 8 | 7 | 110 | 60 | 16 | 0.53 | 5 |
| 401100320260 | 3.15 | 135 | 10 | 8 | 135 | 75 | 18 | 0.8 | 5 |
| 401100530260 | 5.3 | 160 | 13 | 10 | 160 | 90 | 22 | 1.5 | 5 |
| 401100800260 | 8 | 180 | 16 | 13 | 180 | 100 | 26 | 2.3 | 5 |
| 401101120260 | 11.2 | 200 | 18 | 16 | 200 | 110 | 32 | 3.9 | 5 |
| 401101400260 | 14 | 260 | 20 | 18 | 260 | 140 | 36 | 6.35 | 5 |
| 401101700260 | 17 | 300 | 22 | 20 | 300 | 160 | 40 | 9 | 5 |
| 401102120260 | 21.2 | 340 | 26 | 22 | 340 | 180 | 45 | 12.8 | 7 |
| 401103150260 | 31.5 | 350 | 32 | 26 | 350 | 190 | 50 | 17.2 | 7 |

Blueprint

