

Anchorage Point PSA-YEP



Product information



- Rotates through 360° adjustable in the direction of the load.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Passed 150 kg dynamic fall testing (EU standard is 100 kg).
- Meets all requirements of the German BG BAU (Employer-s insurance association of the building industry).
- Correspond to the European Directive for "personnel protection equipment" (89/686/EWG).
- PSA - Lifting point to be as an anchor point for personal protective equipment.

Features: Built-in RFID/NFC chip

Material: Manufactured from forged alloy steel, quenched and tempered

Marking: According to standard, number of persons, standards, individual serial number, manufacturer, production year, product ID

Finish: Yellow Painted

Standard: EN 795, EN 365, EN 50308

| Part Code | Max. number of persons | Torque Nm | thread M | Thread length (E) mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | S mm | W mm | Weight kg | Delivery time |
|-------------|------------------------|-----------|------------|----------------------|------|------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 84158281007 | 1 | 10 | M12 x 1.75 | 19 | 45 | 30 | 10 | 11 | 18 | 33 | 29 | 5 | 45 | 8 | 52 | 0.2 | 20 |
| 84158281015 | 2 | 30 | M16 x 2 | 24 | 52 | 35 | 14 | 13 | 24 | 35 | 33 | 8 | 52 | 10 | 61 | 0.3 | 20 |
| 84158281023 | 2 | 70 | M20 x 2.5 | 30 | 60 | 40 | 16 | 15 | 30 | 44 | 37 | 7 | 60 | 12 | 70 | 0.6 | 20 |

Blueprint

