

## Pipe Lifting TBC - TBC-A



### Product information

Lightweight clamp with pressure resistant plastic cam for vertical concrete pipe lifting

#### Application

- For vertical lifting and transporting of concrete pipes and wells
- Terrier TBC / TBC-A lifting clamps must always be used in pairs (or per three clamps)
- TBC jaw opening available from: 60 to 120 mm
- TBC-A has an extra large jaw opening available from: 50 to 220 mm (adjustable in steps of 25 mm)
- Working load limit (WLL) 1000kg
- Other jaw openings available upon request

#### Features and benefits

- The cam is covered with a special high quality pressure resistant plastic
- Maintenance-friendly clamp, plastic pressure resistant cover is easy to change
- Tough quality welded body
- Lightweight design for easy handling

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 50°C

**Standard:** EN 13155

| Part Code       | Code    | WLL ton | Beam width mm<br>mm | Jaw width mm | S mm | T mm | U mm | W mm | X mm | Y mm | Z mm | Delivery time |
|-----------------|---------|---------|---------------------|--------------|------|------|------|------|------|------|------|---------------|
| 502100101201460 | 1 TBC   | 1       | 60-120              | 60-120       | 169  | 12   | 326  | 97   | 60   | 12   | 40   | 7             |
| 502100102201460 | 1 TBC-A | 1       | 50-220              | 50-220       | 262  | 12   | 459  | 106  | 60   | 12   | 40   | 7             |

# Blueprint

