



## Master link oversized, grade 80

### Product information

Extra large masterlink for chain sling assemblies.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain mm, 1-leg	For chain mm, 2-leg	A mm	B mm	D mm	Weight kg	Delivery time
401100320270	3.2	190	10	7/8	190	100	16	0.86	7
401100640270	6.4	300	13	10	300	210	25	5.53	7
401100700270	7	210	13	10	210	110	22	1.83	5
401101100270	11	300	16	13	300	210	32	5.94	5
401101150270	11.5	270	16	13/16	270	140	28	3.8	5
401101700270	17	270	22	20	270	140	32	5.05	7
401101900270	19	400	22	20	420	220	38	10.78	5
401102800270	25.1	420	26	22	270	140	38	7.29	7
401102700270	27	470	26	22	470	250	45	17.06	7
401104500270	45	380	36	32	380	200	50	17.65	7
401106500270	65	430	36	32	430	220	60	28.85	7

## Blueprint

