



Master link assemblies 3-4-l, grade 80

Product information

Masterlink for 3- and 4-leg chain sling assemblies.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain mm, 3-4-leg	L mm	B mm	D mm	B1 mm	D1 mm	L1 mm	Weight kg	Delivery time
401100240280	2.36	189	6	135	75	18	25	14	54	1.2	5
401100430280	4.25	230	7/8	160	90	22	34	16	70	2.2	5
401100670280	6.7	265	10	180	100	26	40	18	85	3.4	5
401101120280	11.2	315	13	200	110	32	50	22	115	6	5
401101700280	17	400	16	260	140	36	65	26	140	10	5
401102650280	26.5	500	20	350	190	51	70	32	150	23.3	5
401103200280	32	520	22	350	190	51	75	36	170	25.9	5
401104500280	45	570	26	400	200	57	80	40	170	35.2	5
401106700280	67	817	32	460	250	72	190	49	357	67.6	7

Blueprint

