



Pillar Jib Crane Overbraced 270° Movable PFT MOB

Product information

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 270°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

This jib crane is mounted on a movable concrete block provided. Displacement can be done by traveling crane (transport ring) or by forklift.

A full range of accessories is available.

Options

- Hoist power supply cable
- Lockable main switch
- Rotation slowing device
- Rotation stops to weld onto the assembly, or adjustable
- Single- or multipositions rotation lock
- Outdoor use
- Hot dip galvanizing (contact us)
- Electric or manual hoist

Part Code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Delivery time
6025	0.15	150	•	•	•	•	•	•	•	•	•	20
6025	0.25	250	•	•	•	•	•	•	•	-	-	20
6025	0.5	500	•	•	•	-	-	-	-	-	-	20

Technical data

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5	5,5	6
150	x	x	x	x	x	x	x	x	x
250	x	x	x	x	x	x	x		
500	x	x	x						