

Pulley Block KB150-7500

Product information



The pulley blocks from Gebuwin's product range are suitable for both hand and electric winches. The wheel is manufactured from cast iron and fitted with bearings. The pulley blocks are used to guide the cable to the location where the load has to be moved. A fine way to make moving your load easier.

- suitable for electric and manual winches
- pulley wheel made of cast iron
- bracket made of steel with one layer of paint
- plain bearing

Options:

- ATEX suitable

Material: Cast iron, steel

Temperature range: - 20°C up to + 40°C

| Part Code | Rope Ø range | WLL ton | Model | A mm | B mm | C mm | D mm | F mm | G mm | H mm | K mm | M mm | N mm | P mm | Weight kg | Delivery time |
|--------------|--------------|---------|--------|------|------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 140100800490 | 8 | 0.15 | KB150 | 90 | 60 | 18 | 65 | 5 | 11 | 90 | 35 | 54 | 4.5 | 72 | 1 | 20 |
| 140100900490 | 9 | 0.3 | KB300 | 100 | 65 | 20 | 70 | 5 | 11 | 100 | 35 | 59 | 5 | 80 | 1 | 20 |
| 140101000500 | 10 | 0.6 | KB600 | 120 | 65 | 28 | 75 | 5 | 13 | 105 | 35 | 69 | 5.5 | 98 | 1.5 | 20 |
| 140101000501 | 10 | 1.5 | KB1500 | 155 | 110 | 27 | 80 | 6 | 14 | 120 | 75 | 85 | 5.5 | 129 | 3 | 20 |
| 140101600490 | 16 | 2 | KB2000 | 220 | 165 | 32 | 105 | 8 | 17 | 155 | 115 | 121 | 8.5 | 184 | 6.5 | 20 |
| 140101800490 | 18 | 4 | KB4000 | 260 | 200 | 40 | 140 | 10 | 21 | 195 | 145 | 143 | 9.5 | 222 | 11.5 | 20 |
| 140102600490 | 26 | 7.5 | KB7500 | 310 | 240 | 52 | 155 | 12 | 21 | 215 | 180 | 170 | 14 | 250 | 21 | 20 |

Blueprint

