



## Levelling Tool Ganterud

### Product information

This electric levelling tool levels and handles loads efficiently and safely. Due to its high degree of precision, the work becomes more efficient. This reduces both expensive crane time and waiting times. The levelling tool is operated with a user-friendly, IP67-rated remote control.

The Pro models do also offer auto levelling functionality with released chain wheel which makes it easy to find the centre of gravity of the lifted object. Snatch block function with released chain wheel makes rotation of items easy, quick, and safe.

#### Environmental requirements:

- Storage temperature: -20°C up to +45°C
- Relative humidity (RH): 0 – 90% when stored
- IP rating: IP65

#### Handheld controller:

- Number of function keys: 5/7 for Pro models
- Power output: 10 mW
- Power supply: 3X1,5V AAA
- IP rating: IP67

#### Optional equipment:

- Protective cover
- Extended chain
- Extra batteries
- Transport packaging

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +40°C

**Finish:** Ganterud L20-3 Pro: powder coated cover and main body. Ganterud L3 – L5 Pro: durable colored through plastic covers and chromated main body

**Standard:** EN 13155

| Part Code   | Code      | WLL<br>ton | Width<br>mm | Height<br>mm | Chain length<br>m | Chain diam.<br>mm | Depth<br>mm | Load imbalance capacity max.<br>kg | Reversible stroke pr. hook<br>m | Max. leveling length<br>m | Weight<br>kg | Delivery time |
|-------------|-----------|------------|-------------|--------------|-------------------|-------------------|-------------|------------------------------------|---------------------------------|---------------------------|--------------|---------------|
| 5498L31001  | L3        | 3          | 503         | 639          | 3                 | 30,5x10           | 495         | 500                                | 1.5                             | 3 (1,5 + 1,5)             | 130          | 20            |
| 5498L51001  | L5        | 5          | 503         | 639          | 3                 | 30,5x10           | 495         | 750                                | 1.5                             | 3 (1,5 + 1,5)             | 130          | 20            |
| 5498L5P1001 | L5 PRO    | 5          | 503         | 639          | 3                 | 30,5x10           | 495         | 750                                | 1.5                             | 3 (1,5 + 1,5)             | 130          | 20            |
| 5498L203001 | L20-3 PRO | 20         | 712         | 1,050        | 6                 | 60,5x20           | 623         | 3,000                              | 3                               | 6 (3+3)                   | 395          | 20            |