



## Wire Rope Lifting Sling WLS-113

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Both ends mechanically spliced thimbles.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part Code	WLL ton
1603	0.12
1603	0.21
1603	0.32
1603	0.47
1603	0.64
1603	0.82
1603	1.04
1603	1.28

1603	1.55
------	------

1603	1.84
------	------

1603	2.17
------	------

1603	2.51
------	------

1603	3.3
------	-----

1603	4.1
------	-----

1603	5.1
------	-----

1603	6.2
------	-----

1603	7.38
------	------

1603	8.66
------	------

1603	10.04
------	-------

1603	13.12
------	-------

1603	16.59
------	-------

1603	20.56
------	-------

1603	24.78
------	-------

1603	29.55
------	-------

## Technical data