

## Certex Chain Slings CS-265 Grade 80



### Product information



Assembled 2-Legs chain sling with latch hook and grab hook. Slings are equipped with a load plate.

Sling length measured from the top of the master link to the bottom of the hook.

**Material:** Alloy Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Note:** The last three digits of the product code refer to the length: 010 = 1,0 m.

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton
230800600150010	1.6
230800600200010	1.6
230800600250010	1.6
230800600300010	1.6
230800600000010	1.6
230800800200010	2.8
230800800250010	2.8

230800800300010	2.8
230800800000010	2.8
230801000200010	4.25
230801000250010	4.25
230801000300010	4.25
230801000350010	4.25
230801000000010	4.25
230801300250010	7.5
230801300300010	7.5
230801300350010	7.5
230801300400010	7.5
230801300000010	7.5
230801600300010	11.2
230801600350010	11.2
230801600400010	11.2
230801600450010	11.2
230801600000010	11.2
230802000400010	17.5
230802000500010	17.5
230802000000010	17.5