

## Basic-Lift AERO

### Product information



moving limits



The BASIC-LIFT is an all-rounder complementing the tried and tested AERO-LIFT® range of vacuum lifters. Without battery or inconvenient power cables and thus purely mechanical, it is absolutely independent. But yet this type can lift loads of 1.200 kg and above.

Its safety is additionally guaranteed by vacuum gauge and a battery-operated warning device and meets the requirements of the EU norm EN 13155.

Handling is extremely easy. Every time the lifter is put down it automatically switches from „Suction“ to „Release“ and vice versa.

Part Code	Code	WLL ton	Min. load kg	Plate Ø mm	Main beam length mm	Cross beam width mm	Weight kg	Delivery time
56051016000	BL 100 / 1L	0.1	2	1 / 230	-	-	15	20
56051016001	BL 400 / 1L	0.4	2	1 / 410	-	-	55	20
56051016002	BL 400 / 4L	0.4	3	4 / 280	2.2	1	100	20
56051016003	BL 600 / 2L	0.6	3	2 / 410	2.2	-	90	20
56051016005	BL 600 / 4L	0.6	3	4 / 340	2.2	1	115	20
56051016004	BL 600 / 3L	0.6	3	3 / 410	2.2	-	140	20
56051016006	BL 600 / 6L	0.6	3	6 / 280	2.2	1	140	20
56051016007	BL 600 / 8L	0.6	3	8 / 280	4	1	200	20
56051016008	BL 750 / 6L	0.75	3	6 / 340	4	1	160	20
56051016009	BL 900 / 6L	0.9	3	6 / 280	2.2	1	135	20
56051016010	BL 1200 / 4L	1.2	5	4 / 410	2.2	1	195	20
56051016011	BL 1200 / 6L	1.2	5	6 / 410	2.2	1	220	20
56051016012	BL 1200 / 8L	1.2	5	8 / 340	3	1	230	20