



Pillar Jib Crane Type SK-IL

Product information



We recommend this type of pillar jib crane when the lifting height is limited. Our standard programme has been designed in load groups from 125 kg up to 3.200 kg. This type of crane has been designed without counter bracing which maximises the lifting height considerably. All these cranes have been designed with an IPE-profile jib arm, which is ideal for use together with an electrical trolley. The jib cranes are assembled with a separate C-profile for cable, hose etc.

Proof load: Usually 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Part Code	WLL ton	Type	Max. hoist weight kg	IPE	Flange width mm	L mm	L1 mm	H mm	H1 mm	H2 mm	Ø D mm	Weight kg	Delivery time
60255230012000	0.125	SK-IL-125/2	40	120	64	2,000	500	4,000	750	3,820	430	165	20
60255230013000	0.125	SK-IL-125/3	40	200	100	3,000	500	4,000	750	3,740	430	165	20
60255230014000	0.125	SK-IL-125/4	40	240	120	4,000	500	4,000	750	3,700	430	165	20
60255230015000	0.125	SK-IL-125/5	40	300	150	5,000	500	4,000	750	3,640	430	165	20
60255230022000	0.25	SK-IL-250/2	45	180	91	2,000	500	4,000	750	3,760	430	295	20
60255230023000	0.25	SK-IL-250/3	45	220	110	3,000	500	4,000	750	3,720	430	295	20
60255230024000	0.25	SK-IL-250/4	45	300	150	4,000	500	4,000	750	3,670	430	295	20
60255230025000	0.25	SK-IL-250/5	45	330	160	5,000	500	4,000	750	3,610	580	295	20
60255230052000	0.5	SK-IL-500/2	55	200	100	2,000	500	4,000	750	3,740	430	555	20
60255230053000	0.5	SK-IL-500/3	55	270	135	3,000	500	4,000	750	3,670	580	555	20
60255230054000	0.5	SK-IL-500/4	55	300	150	4,000	500	4,000	750	3,640	580	555	20
60255230055000	0.5	SK-IL-500/5	55	360	170	5,000	500	4,000	1,000	3,560	680	555	20
60255230102000	1	SK-IL-1000/2	58	270	110	2,000	500	4,000	750	3,720	580	1,058	20
60255230103000	1	SK-IL-1000/3	58	400	160	3,000	500	4,000	750	3,610	580	1,058	20
60255230104000	1	SK-IL-1000/4	58	400	180	4,000	500	4,000	1,000	3,510	680	1,058	20
60255230202000	2	SK-IL-2000/2	88	270	135	2,000	500	4,000	750	3,650	680	2,088	20
60255230203000	2	SK-IL-2000/3	88	360	170	3,000	500	4,000	1,000	3,560	810	2,088	20
60255230204000	2	SK-IL-2000/4	88	450	190	4,000	500	4,000	1,000	3,470	810	2,088	20