

## Wall Mounted Jib Crane Type VK-IL

### Product information



### CERTEX

**General:** We recommend this type of wall jib crane when the lifting height is limited. Our standard programme has been designed in load groups from 125 kg up to 3200 kg. This type of jib crane has been designed without counter bracing which maximises the lifting height considerably.

All these wall mounted swing cranes have been designed with an IPE-profile jib arm which is ideal for use together with an electrical trolley. If using a manual trolley we can offer to deliver the jib arm mounted with a smooth running C-profile.

The jib cranes are assembled with a separate C-profile for cable, hose etc.

**Proof load:** Usually 1,5 x WLL.

**Material:** Beam and plate of high-strength structural steel.

**Marking:** Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

**Finish:** Yellow painted. Other treatments available on request.

Part Code	WLL	Type	Max. hoist weight kg	IPE	Flange width mm	Weight kg	Delivery time
60255330012000	0.125	VK-IL-125/2	40	120	64	165	20
60255330013000	0.125	VK-IL-125/3	40	180	91	165	20
60255330014000	0.125	VK-IL-125/4	40	220	110	165	20
60255330015000	0.125	VK-IL-125/5	40	240	120	165	20
60255330022000	0.25	VK-IL-250/2	45	140	73	295	20
60255330023000	0.25	VK-IL-250/3	45	200	100	295	20
60255330024000	0.25	VK-IL-250/4	45	240	120	295	20
60255330025000	0.25	VK-IL-250/5	45	300	150	295	20
60255330052000	0.5	VK-IL-500/2	55	180	91	555	20
60255330053000	0.5	VK-IL-500/3	55	240	120	555	20
60255330054000	0.5	VK-IL-500/4	55	300	150	555	20
60255330055000	0.5	VK-IL-500/5	55	330	160	555	20
60255330102000	1	VK-IL-1000/2	58	200	100	1,058	20
60255330103000	1	VK-IL-1000/3	58	270	135	1,058	20
60255330104000	1	VK-IL-1000/4	58	330	160	1,058	20

## Blueprint

