

General use



Agriculture and livestock



Winch rope



Stay rope



Slings



Steel Wire Rope ROPETEX S33 Stainless Steel

Product information









Steel wire rope ROPETEX S33 in stainless steel is a good choice for basic lifting applications in environments where corrosion resistance is important.

ROPETEX S33 is equipped with a Wire Strand Core (WSC) which gives the rope a good strength and a reasonable balance between fatigue and wear resistance.

ROPETEX S33 can be used for applications where the rope runs over sheaves or is spooled on a drum.

Typical applications:

- · lifting applications
- slings
- winch rope
- stay ropes

Rope construction: 6x19M-WSC Material: AISI316 / EN 1.4401 Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4 except material

Fill factor: 0,53

Part Code	Rope Diameter,	Tensile strength N/mm²	Finish	Rope lay	Min. Breaking force kN.	Steel area mm²	Lubrication	Weight	Delivery time
108100204620038	2	-	-	-	-	-	-	-	-
108100304620038	3	-	-	-	-	-	-	-	-
108100404620038	4	-	-	-	-	-	-	-	-
108100504620038	5	-	-	-	-	-	-	-	-
108100604620038	6	-	-	-	-	-	-	-	-
108100704620038	7	-	-	-	-	-	-	-	-
108100804620038	8	-	-	-	-	-	-	-	-
108101004620038	10	-	-	-	-	-	-	-	-
108101204620038	12	-	-	-	-	-	-	-	-
108101404620038	14	-	-	-	-	-	-	-	-
108101604620038	16	-	-	-	-	-	-	-	-