

## Web Lashing POWERTEX Trucker Force

### Product information



### POWERTEX



POWERTEX Trucker Force web lashings are available as 2-part lashings as standard and intended for everyday use by professional haulers.

Heavy duty lashing made of high strength polyester yarn and steel ratchets and hooks.

Suitable for professional transporters looking for extra high strength and extra high STF.

- Strong and durable with LC 2500 daN and extra high STF of 500 daN
- Webbing having min breaking strength of 7500 daN
- Blue webbing with 5 + 5 black stripes for easy identification
- Both long part and short part carry blue identification labels
- Label gives information on STF and lashing capacity for different lashing connections
- Each part is marked with a unique serial number for safe equipment registration
- The blue information label is protected by additional layer of transparent plastic for long life
- Year/Month calendar printed on the label where latest inspection date can be marked or punched
- All lashings carry a white label with important warning instructions and user instruction pictogram
- Each lashing marked with QR code to access full user manual
- Cr6 free galvanization – better for health and environment
- Trucker can be supplied with other lengths and other end fittings on request.

**Safety factor:** Webbing min. 3, Ratchets min. 2 and Hooks min. 2

**Material:** Polyester and steel

**Marking:** According to standard, POWERTEX, LC, STF, length, manufacturing year, batch number, serial number, QR code, inspection calendar, user warning instructions

**Temperature range:** -40°C up to +120°C

**Standard:** EN 12195-2

**Note:** Protect the lashings from sharp edges

Part Code	LC daN	2xLC (daN)	Length m	Width	Design	Fitting	STF daN	Colour	Delivery time
-----------	--------	------------	----------	-------	--------	---------	---------	--------	---------------

701401002200190	2,500	5,000	10	50	2-part	Wire hook double	500	Blue	20
-----------------	-------	-------	----	----	--------	------------------	-----	------	----