



Short Bow Socket SBS

Product information

General: The "ultimate" socket for dynamic loads. Towing lines, anchor lines and chain-rope connections used by major offshore contractors. Quenched and tempered cast steel with extremely high mechanical values for unmatched weight to MBL ratio. All spelter sockets have a 100% efficiency on wire rope MBL.

The standard finish of our sockets is blue. Hot dipped galvanized is also available.

Standard: EN 10204-2.1 declaration of conformity / EN 10204-3.1 material certificate.

Option: Hot dip galvanized.

Material: Quenched and tempered cast steel.

Part Code	Rope Ø range mm	MBL	Finish	Model no.	For wire Ø inch	Weight kg	Delivery time
122103600205	31-36	140	Painted	SBS 512	11/4 - 13/8	7	20
122104200205	37-42	160	Painted	SBS 517	11/2 - 15/8	10	20
122104800205	43-48	200	Painted	SBS 519	13/4 - 17/8	16	20
122105400205	49-54	250	Painted	SBS 522	2 - 21/8	21	20
122106000205	55-60	320	Painted	SBS 524	21/4 - 23/8	28	20
122106800205	61-68	400	Painted	SBS 526	21/2 - 25/8	44	20
122107500205	69-75	500	Painted	SBS 527	23/4 - 27/8	53	20
122108000205	76-80	600	Painted	SBS 528	3 - 35/8	70	20
122108600205	81-86	700	Painted	SBS 529	31/4 - 33/8	81	20
122109300205	87-93	800	Painted	SBS 530	31/2 - 35/8	112	20
122110200205	94-102	900	Painted	SBS 531	33/4 - 4	130	20
122111500205	108-115	1,000	Painted	SBS 533	41/4 - 41/2	182	20

Blueprint

