

Elektrinis telferis SWF NOVA Blackline

Produkto informacija



General: The NOVA Blackline meets the high demands of a SWF hoist in regards to safety, quality and reliability.

- Ultimate load from 2-12,5 tons and a lifting weight up to 12 meters
- Optimal space and land utilization due to compact headroom and optimum hook dimension
- Minimized attrition of rope by a big drum diameter
- Robust contactor control for hoist motor and trolley motor
- Mechanical overload protection protects crane and building structure
- Plug and play - quick and easy installation and maintenance
- Overheat protection

Produkto kodas	Tipas	Kėlimo aukštis m	Maks. apkrova kg	FEM	Kėlimo greitis m/min.	ISO	Pervažiavimo greitis m/min	Pristatymo laikas
6041	NOVA BB	6	2 000	2m	5/0,8	M5	20/5	20
6041	NOVA BB	9,5	2 000	2m	5/0,8	M5	20/5	20
6041	NOVA BB	6	2 500	3m	5/0,8	M6	20/5	20
6041	NOVA BB	9,5	2 500	3m	5/0,8	M6	20/5	20
6041	NOVA BB	6	3 200	2m	5/0,8	M5	20/5	20
6041	NOVA BB	9,5	3 200	2m	5/0,8	M5	20/5	20
6041	NOVA BC	6	4 000	3m	5/0,8	M6	20/5	20
6041	NOVA BC	9	4 000	3m	5/0,8	M6	20/5	20
6041	NOVA BC	6	5 000	2m	5/0,8	M5	20/5	20
6041	NOVA BC	9	5 000	2m	5/0,8	M5	20/5	20
6041	NOVA BC	6	6 300	1Am	4/0,7	M4	20/5	20
6041	NOVA BC	9	6 300	1Am	4/0,7	M4	20/5	20
6041	NOVA BD	9	8 000	3m	5/0,8	M6	20/5	20
6041	NOVA BD	12	8 000	3m	5/0,8	M6	20/5	20
6041	NOVA BD	9	10 000	2m	5/0,8	M5	20/5	20
6041	NOVA BD	12	10 000	2m	5/0,8	M5	20/5	20
6041	NOVA BD	9	12 500	1Am	4/0,7	M4	24/6	20
6041	NOVA BD	12	12 500	1Am	4/0,7	M4	24/6	20